

## **Braked Noise reducing castors 100mm** wheel

## 100-3360-HUR/SWB

Noise reducing swivel braked castor with a 100mm diameter wheel. This specialist noise reducing castor wheel has a hard nylon outer with solid elastic rubber centre giving maximum durability with minimum noise. With a load rating of up to 160kg per castor it is ideal for roll cages or supermarket cage trolleys. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



## **Technical Specifications**

	Bearing Type	Roller Bearing
<b>E</b>	Colour	No
0	Hardness of Tread	D75
KG	Load Capacity (kg)	160
KG	Load Capacity Dynamic (kg)	160
KG X4	Max Load Capacity of 4 Castors	480
	Plate Dimension Length (mm)	105
<u> </u>	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
W.	Plate Hole Diameter	8
٥	Product Type	Top Plate Castors
	Product Type Swivel Radius	Top Plate Castors
٥		
<b>3</b>	Swivel Radius	91
<b>♡</b>   <b>♂</b>	Swivel Radius Temperature Range	91 -20 min to +60 max
	Swivel Radius Temperature Range Thread Material	91 -20 min to +60 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	91 -20 min to +60 max No 128
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)	91 -20 min to +60 max No 128 36
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)  Wheel Centre	91 -20 min to +60 max No 128 36 Rubber
	Swivel Radius  Temperature Range  Thread Material  Total Castor Height  Tread Width (mm)  Wheel Centre  Wheel Colour	91 -20 min to +60 max No 128 36 Rubber White

## **Dimensions**

