





















125mm Swivel Braked Castor Grey Rubber Wheel

125-3360-GVR/SWB

This 125mm braked castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the non marking grey rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking grey rubber wheel with roller bearings means the castor is quiet to move, will not mark the floor. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	A80
	Load Capacity (kg)	100
	Max Load Capacity of 4 Castors	300
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	123
	Temperature Range	-20 min to +80 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	23
	Wheel Centre	Black Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	125
	Wheel Material	Grey Rubber

Dimensions

