





















125mm Thermoplastic Rubber Castors with Brake

125-3360-MGR/SWB

This Rubber Caster Wheel is 125mm diameter and made of Thermoplastic Rubber with a bonded on polypropylene wheel centre. This bonded rubber castor can take higher loads compared to a standard rubber wheel and the bonding process prevents tyre shear. With all the benefits of a non marking grey rubber wheel this castor is more competitively priced, hard wearing and longlasting. The easy foot operated brake locks the swivel and wheel into position.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	88 shore A
	Load Capacity (kg)	150
	Manufacturer Part No.	TSZ7 MGR 125/30 P2 BP
	Max Load Capacity of 4 Castors	450
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	103
	Temperature Range	-20 min to +60 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	40
	Wheel Centre	Grey Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	125
	Wheel Material	Rubber

Dimensions

