





















## 125mm Swivel Castor with Brake White Nylon Wheel

### 125-3360-NYB/SWB

This 125mm braked castors is made of a zinc plated housing which ensures the castor is robust and suitable for a variety of environments. The braked swiveling castors, with the white nylon wheel is strong robust and durable and suitable for moving machinery and equipment. The white nylon wheel castors contains roller bearings making it easier to move whilst maintaining core strength. The foot operated wheel brake on these castors simultaneously brakes both the swivel castor head and the wheel.



### Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D75
	Load Capacity (kg)	300
	Manufacturer Part No.	TSZ7 NSR 125/40 P2 BP
	Max Load Capacity of 4 Castors	900
	Plate Dimension Length (mm)	105
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Swivel Radius	123
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	38
	Wheel Centre	White Polyamide
	Wheel Colour	White
	Wheel Diameter(mm)	125
	Wheel Material	Nylon

### Dimensions

