

125mm Fixed Castors Polyurethane Wheel

125-3368-PNB

This 125mm fixed polyurethane casters is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. This fixed castor with the polyurethane wheel is strong and durable and suitable for moving machinery and equipment. The polyurethane tire is bonded onto the polyamide nylon centre making the castor strong and durable. Fixed castors can be teamed up with swiveling and braked castors for maximum control when moving.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D60
	Load Capacity (kg)	250
	Manufacturer Part No.	TSZ7 NPR 125/30 P2 FA
	Max Load Capacity of 4 Castors	750
	Plate Dimension Length (mm)	101
	Plate Dimension Width (mm)	85
	Plate Hole Centres Length (mm)	80/77
	Plate Hole Centres Width (mm)	60
	Plate Hole Diameter	8
	Product Type	Top Plate Castors
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	155
	Tread Width (mm)	30
	Wheel Centre	White Polyamide
	Wheel Colour	Maroon
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

