

125mm Heavy Duty Leading Brake Castors White Nylon Wheel

125-5000-NYB/FR

Leading Brake Castors are ideal for applications where when moving equipment you do not want the foot operated brake pedal to be lost under the equipment. No following brake flutter, and foot pedal easily accessed. These Leading Brake added to our heavy duty 5000 Series castors for heavy duty applications



Technical Specifications

	Bearing Type	Ball Journal
53	Colour	No
0	Hardness of Tread	D75
KG	Load Capacity (kg)	700
KQ X4	Max Load Capacity of 4 Castors	2100
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
) i	Plate Hole Centres Width (mm)	80/75
***	Plate Hole Diameter	10
٥	Product Type	Top Plate Castors
☼ ७	Product Type Swivel Radius	Top Plate Castors
		•
\$	Swivel Radius	168
<u>₩</u>	Swivel Radius Temperature Range	-40 min to +80 max
	Swivel Radius Temperature Range Thread Material	168 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	168 -40 min to +80 max No 164
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	168 -40 min to +80 max No 164 50
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	168 -40 min to +80 max No 164 50 Nylon

Dimensions





