

125mm Heavy Duty Leading Brake Castors with Polyurethane Wheel

125-5000-PAL/FR

Leading Brake Castors are ideal for applications where when moving equipment you do not want the foot operated brake pedal to be lost under the equipment. No following brake flutter, and foot pedal easily accessed. These Leading Brake added to our heavy duty 5000 Series castors for heavy duty applications



Technical Specifications

٧	Bearing Type	Ball Journal
S	Colour	No
0	Hardness of Tread	92 shore A
KG	Load Capacity (kg)	500
x4	Max Load Capacity of 4 Castors	1500
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
***	Plate Hole Diameter	10
٥	Product Type	Top Plate Castors
<i>উ</i>	Swivel Radius	168
	Temperature Range	-20 min to +60 max
<u> </u>	Thread Material	No
<u>w</u> i	Total Castor Height	164
₽	Tread Width (mm)	50
	Wheel Centre	Aluminum
0	Wheel Colour	Yellow
$\overline{\bigcirc}$	Wheel Diameter(mm)	125
0	Wheel Material	Polyurethane

Dimensions





