





















125mm Heavy Duty Braked Castors Polyurethane Wheel 550kg

125-5000-SUB/SWB

These 125mm extra heavy duty lockable castors are made of a heavy duty pressed steel zinc plated, housing a 5" (125mm) polyurethane wheel mounted on a cast iron centre. These 5" heavy duty polyurethane caster wheels run on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These castors are suitable for a range of heavy duty applications. Able to carry loads of 550kgs each castor, combine 4 to carry 1.5 tonnes. Overall height 164mm, 4 x M10 Bolt Fixing top plate castors for easy attachment, in stock for NEXT DAY delivery!



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	550
	Max Load Capacity of 4 Castors	1650
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	148
	Temperature Range	-40 min to + 60 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

