





















## 125mm Heavy Duty Castors Polyurethane Wheel 550kg

### 125-5000-SUB

These extra **heavy duty swivel castors** are 164mm overall height, 4 x M10 Bolt fixing plate, castor housing made of a heavy duty pressed steel zinc plated, with a 5" ( 125mm ) polyurethane wheel on a cast iron centre. This swiveling castors wheel runs on ball journal bearings, making heavier loads easier to move. These swiveling castors are suitable for a range of heavy duty applications, able to carry loads 550kgs each. Combine 4 x 5" heavy duty polyurethane castors to carry over 1.5 tonnes



### Technical Specifications

	Bearing Type	Ball Journal
	Colour	Yellow
	Hardness of Tread	A92
	Load Capacity (kg)	550
	Max Load Capacity of 4 Castors	1650
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	118
	Temperature Range	-40 min to + 60 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

### Dimensions

