

125mm Fixed Heavy Duty Castors




















Polyurethane Wheel 550kg

125-5050-SUB

These 5" heavy duty fixed castors are made of a heavy duty pressed steel zinc plated, housing a polyurethane wheel mounted on a cast iron centre. This fixed castor wheel runs on ball journal bearings, making the heavier loads easier to move. These castors are suitable for a range of heavy duty applications. Overall height 164mm, load capacity 550kgs per fixed caster wheel, 4 x M10 Bolt Fixing Plate, making these heavy duty fixed castors easy to fix, move and combine 4 castors to carry over 1.5 tonnes castors.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	550
	Max Load Capacity of 4 Castors	1650
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Temperature Range	-40 min to + 60 max
	Thread Material	No
	Total Castor Height	164
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	125
	Wheel Material	Polyurethane

Dimensions

