

150mm Apex Heavy Duty Swivel Castors with Polyurethane Aluminium Wheel

150-5000-APEX

These 150mm extra heavy duty swivel castors made of a heavy duty pressed steel zinc plated, housing a polyurethane wheel on an aluminium centre. Overall height 200mm, load capacity 700kgs each, 4 x M10 Bolt Fixing Plate for easy attachment. This heavy duty swivelling castor wheel runs on ball journal bearings, making heavier oads easier to move. These heavy duty polyurethane castor wheels are strong and durable, suitable for a range of heavy duty applications. Combine 4 of these castors to carry 2 tonne castors.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
0	Hardness of Tread	A87
KG	Load Capacity (kg)	454
KG X4	Max Load Capacity of 4 Castors	1362
	Plate Dimension Length (mm)	140
<u> </u>	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
I	Plate Hole Centres Width (mm)	80/75
N/K	Plate Hole Diameter	10
٠	Product Type	Top Plate Castors
4 S	rroddet rype	
<u></u>	Swivel Radius	135
<u></u>	Swivel Radius	135
<u></u>	Swivel Radius Temperature Range	135 -20 min to + 60 max
	Swivel Radius Temperature Range Thread Material	135 -20 min to + 60 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	135 -20 min to + 60 max No 195
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	135 -20 min to + 60 max No 195
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	135 -20 min to + 60 max No 195 50 Aluminium
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	135 -20 min to + 60 max No 195 50 Aluminium Yellow

Dimensions

