





















## 160mm Swivel Braked Castor Grey Rubber Wheel

### 160-3360-GVR/SWB

This 160mm braked castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the non marking grey rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking grey rubber wheel with roller bearings means the castor is quiet to move, will not mark the floor. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



### Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	A80
	Load Capacity (kg)	150
	Max Load Capacity of 4 Castors	450
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	167
	Temperature Range	-20 min to +80 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	25
	Wheel Centre	Black Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	160
	Wheel Material	Grey Rubber

### Dimensions

