





















160mm Thermoplastic Rubber Castors with Brake

160-3360-MGR/SWB

This Rubber Caster Wheel is 160mm diameter and made of Thermoplastic Rubber with a bonded on polypropylene wheel centre. This bonded rubber castor can take higher loads compared to a standard rubber wheel and the bonding process prevents tyre shear. With all the benefits of a non marking grey rubber wheel this castor is more competitively priced, hard wearing and longlasting. The easy foot operated brake locks the swivel and wheel into position.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	88 shore A
	Load Capacity (kg)	200
	Manufacturer Part No.	TSZ7 MGR 160/40 P3 BP
	Max Load Capacity of 4 Castors	600
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	135
	Temperature Range	-20 min to +60 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	40
	Wheel Centre	Grey Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	160
	Wheel Material	Rubber

Dimensions

