

## 160mm Fixed Castor with a Balck Rubber Wheel with a Metal Centre

## 160-3368-MPVR

This 160mm diameter medium duty fixed castor, with a solid black rubber wheel, is ideal for a large variety of applications. A fixed caster, has a fixed metal frame that supports the rubber wheel, and does not allow the wheel to swivel, enabling controlled uni-directional movement. Fixed castor wheels are often teamed up with swivel casters on equipment and trolleys for a controlled movement. With a top plate for easy attachment, you can also purchase our M10 Bolts and M10 Nuts, which are ideal for attaching to your castor for your application.



## **Technical Specifications**

	Bearing Type	Roller
59	Colour	No
0	Hardness of Tread	A80
KG	Load Capacity (kg)	160
KG X4	Max Load Capacity of 4 Castors	480
(b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	Plate Dimension Length (mm)	140
2 1	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80
**	Plate Hole Diameter	10
~		
٥	Product Type	Top Plate Castors
₩ 3	Product Type Swivel Radius	Top Plate Castors
	Swivel Radius	N/A
<u>I</u>	Swivel Radius Thread Material	N/A No
<u>₹</u> 1	Swivel Radius Thread Material Total Castor Height	N/A No 200
1 1 3 1 .9.	Swivel Radius Thread Material Total Castor Height Tread Width (mm)	N/A No 200 25
1 1 3 1 .9.	Swivel Radius Thread Material Total Castor Height Tread Width (mm) Wheel Centre	N/A No 200 25 Metal
	Swivel Radius Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	N/A No 200 25 Metal Black

## **Dimensions**





