

160mm Heavy Duty Rubber Castor Wheel with Leading Brake

160-5000-HRT/FR

Leading Brake Castors are ideal for applications where when moving equipment you do not want the foot-operated brake pedal to be lost under the equipment. No following brake flutter and foot pedal easily accessed. These Leading Brake added to our 5000 Series heavy duty casters.



Technical Specifications

| | | |
|---|--------------------------------|--------------------|
|  | Bearing Type | Ball Journal |
|  | Colour | No |
|  | Hardness of Tread | 75 shore A |
|  | Load Capacity (kg) | 400 |
|  | Max Load Capacity of 4 Castors | 1200 |
|  | Plate Dimension Length (mm) | 140 |
|  | Plate Dimension Width (mm) | 110 |
|  | Plate Hole Centres Length (mm) | 105 |
|  | Plate Hole Centres Width (mm) | 80/75 |
|  | Plate Hole Diameter | 10 |
|  | Product Type | Top Plate Castors |
|  | Swivel Radius | 170 |
|  | Temperature Range | -20 min to +85 max |
|  | Thread Material | No |
|  | Total Castor Height | 200 |
|  | Tread Width (mm) | 50 |
|  | Wheel Centre | Aluminum |
|  | Wheel Colour | Black |
|  | Wheel Diameter(mm) | 160 |
|  | Wheel Material | Rubber |

Dimensions

