

160mm Heavy Duty Nylon Castor Wheel with Directional Lock

160-5000-NYB/D

Directional Lock added to our 160mm nylon caster wheels. A directional lock is a way of making a swivel castor into a fixed castor temporarily - by locking the swivel head but not the wheel which means castor moves in one direction. Directional lock castors are great for cornering or pivoting. Can be added to just one trolley wheel - usually, front left of the trolley if left cornering or front right if right cornering.



Technical Specifications

	Bearing Type	Ball Journal
59	Colour	No
0	Hardness of Tread	D75
KG	Load Capacity (kg)	700
KG X4	Max Load Capacity of 4 Castors	2100
<u>> </u>	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
W _K	Plate Hole Diameter	10
4 ⁹ Ca	Deadust Tune	Top Plate Castors
٠	Product Type	Top Plate Castors
<u>~</u>	Swivel Radius	150
	• •	
3	Swivel Radius	150
<u></u>	Swivel Radius Temperature Range	150 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	150 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	150 -40 min to +80 max No 200
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	150 -40 min to +80 max No 200
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	150 -40 min to +80 max No 200 50 Nylon
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	150 -40 min to +80 max No 200 50 Nylon White

Dimensions

