

160mm Heavy Duty Castors with Leading Brake Nylon Wheel

160-5000-NYB/FR

Leading Brake Castors are ideal for applications where when moving equipment you do not want the foot operated brake pedal to be lost under the equipment. No following brake flutter, and foot pedal easily accessed. These Leading Brake added to our heavy duty 5000 Series castors for heavy duty applications.



Technical Specifications

٧	Bearing Type	Ball Journal
53	Colour	No
0	Hardness of Tread	D75
KG	Load Capacity (kg)	700
KG X4	Max Load Capacity of 4 Castors	2100
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
**	Plate Hole Diameter	10
495		
٥	Product Type	Top Plate Castors
r V	Product Type Swivel Radius	170
ड	Swivel Radius	170
₩ L	Swivel Radius Temperature Range	170 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	170 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	170 -40 min to +80 max No 200
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	170 -40 min to +80 max No 200
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	170 -40 min to +80 max No 200 50 Nylon
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	170 -40 min to +80 max No 200 50 Nylon White

Dimensions

