












160mm Heavy Duty Castors with Brake Polyurethane Wheel

160-5000-PAL/SWB

This 160mm extra heavy-duty castor is made of a pressed steel zinc plated, housing a polyurethane wheel mounted on an aluminium centre. This castor wheel runs on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These castors are suitable for a range of heavy duty applications, carrying 700kgs each castor wheel, overall height 200mm 4 x M10 Bolt Fixing Plate. Combine 4 of these to carry over 2 tonnes castors.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	700
	Max Load Capacity of 4 Castors	2100
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	150
	Temperature Range	-20 min to + 60 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	50
	Wheel Centre	Aluminium
	Wheel Colour	Yellow
	Wheel Diameter(mm)	160
	Wheel Material	Polyurethane

Dimensions

