

160mm Heavy Duty Fixed Castors













Polyurethane Wheel 700kg

160-5050-PAL

These 160mm extra heavy duty fixed castors are made of a heavy duty pressed steel zinc plated, housing a polyurethane wheel mounted on an aluminium centre. This 6" fixed castor wheel runs on ball journal bearings, making the heavier loads easier to move. These castors are suitable for a range of heavy duty applications. Load capacity per fixed castors is 700kgs making a combination of 4 castors able to carry over 2 tonnes. Overall height 200mm easily attached via 4 x M10 Bolt fixing top plate.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	700
	Max Load Capacity of 4 Castors	2100
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Temperature Range	-20 min to + 60 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	50
	Wheel Centre	Aluminium
	Wheel Colour	Yellow
	Wheel Diameter(mm)	160
	Wheel Material	Polyurethane

Dimensions

