

160mm Heavy Duty Fixed Castors

















Polyurethane Wheel 700kg

160-5050-SUB

These 160mm extra heavy duty fixed castors are able to carry loads of 700kgs each, making them in sets of four 2 tonne castors! Made of a heavy duty pressed steel zinc plated, housing a 160mm (6") polyurethane wheel mounted on a strong cast iron centre. This fixed castor wheel runs on ball journal bearings, making the heavier loads easier to move. These fixed heavy duty castors are suitable for a range of heavy duty and industrial applications.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A92
	Load Capacity (kg)	700
	Max Load Capacity of 4 Castors	2100
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Temperature Range	-40 min to + 60 max
	Thread Material	No
	Total Castor Height	200
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	160
	Wheel Material	Polyurethane

Dimensions

