

200mm Swivel Braked Castor Grey Rubber Wheel

200-3360-GVR/SWB

This 200mm braked castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the non marking grey rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking grey rubber wheel with roller bearings means the castor is quiet to move, will not mark the floor. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

| | Bearing Type | Roller |
|---|--|---|
| 53 | Colour | No |
| 0 | Hardness of Tread | A80 |
| KG | Load Capacity (kg) | 200 |
| ×G ×4 | Max Load Capacity of 4 Castors | 600 |
| () () + | Plate Dimension Length (mm) | 137 |
| | Plate Dimension Width (mm) | 105 |
| | Plate Hole Centres Length (mm) | 105 |
| | Plate Hole Centres Width (mm) | 80/75 |
| N/K | Plate Hole Diameter | 10 |
| ٥ | Product Type | Top Plate Castors |
| | | |
| <u>~</u> | Swivel Radius | 167 |
| 1 | Swivel Radius Temperature Range | 167 -20 min to +80 max |
| | | - |
| 1 | Temperature Range | -20 min to +80 max |
| <u>II</u> | Temperature Range Thread Material | -20 min to +80 max |
| <u>I</u> | Temperature Range Thread Material Total Castor Height | -20 min to +80 max No 240 |
| <u>I</u> <u>I</u> <u>J</u> | Temperature Range Thread Material Total Castor Height Tread Width (mm) | -20 min to +80 max No 240 |
| | Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre | -20 min to +80 max No 240 33 Black Polypropylene |
| | Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour | -20 min to +80 max No 240 33 Black Polypropylene Grey |

Dimensions





