

## 200mm Swivel Nylon Castors with Brake 200-3360-NY/SWB


This 200mm braked castors are made of a zinc plated housing which ensures the castors are robust enough and suitable for a variety of environments. The braked swiveling castors, with the white nylon wheel are strong robust and durable and suitable for moving machinery and equipment. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These 8" Nylon Castors with a brake can carry loads of 400kgs each.




## **Technical Specifications**

Ô	Bearing Type	Plain
5	Colour	No
0	Hardness of Tread	D75
KG	Load Capacity (kg)	400
KG X4	Max Load Capacity of 4 Castors	1200
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
W.	Plate Hole Diameter	10
٢	Product Type	Top Plate Castors
€	Product Type Swivel Radius	Top Plate Castors
10.14		
3	Swivel Radius	167
	Swivel Radius Temperature Range	167 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	167 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	167 -40 min to +80 max No 240
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	167 -40 min to +80 max No 240 46
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	167 -40 min to +80 max No 240 46 White Polyamide
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	167 -40 min to +80 max No 240 46 White Polyamide White

## Dimensions







Email: sales@rosscastors.co.uk

Ross Handling 1 Tuxford Road Leicester LE4 9TZ