

200mm Red Polyurethane Castor Wheel with Directional Lock

200-3360-PNB/D

Directional lock added to our 200mm polyurethane wheel. Directional lock is a way of making a swivel castor into a fixed castor temporarily - by locking the swivel head but not the wheel which means castor moves in one direction. Directional lock castors are great for cornering or pivoting. Can be added to just one trolley wheel - usually front left of the trolley if left cornering or front right if right cornering.



Technical Specifications

٥	Bearing Type	Roller
53	Colour	No
0	Hardness of Tread	D60
KG	Load Capacity (kg)	400
KG X4	Max Load Capacity of 4 Castors	1200
(b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
W.	Plate Hole Diameter	10
49h		
٥	Product Type	Top Plate Castors
<u>v</u>	Product Type Swivel Radius	155
₫	Swivel Radius	155
<u>.</u>	Swivel Radius Temperature Range	155 -40 min to +80 max
	Swivel Radius Temperature Range Thread Material	155 -40 min to +80 max No
	Swivel Radius Temperature Range Thread Material Total Castor Height	155 -40 min to +80 max No 240
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm)	155 -40 min to +80 max No 240 50
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre	155 -40 min to +80 max No 240 50 White Polyamide
	Swivel Radius Temperature Range Thread Material Total Castor Height Tread Width (mm) Wheel Centre Wheel Colour	155 -40 min to +80 max No 240 50 White Polyamide Maroon

Dimensions





