





















200mm Heavy Duty Polyurethane Swivel Castor with Brake 400kg Load

200-3360-PNB/SWB

This 200mm braked polyurethane castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The braked swivel castor features a strong and durable polyurethane wheel suitable for moving machinery and equipment. The polyurethane tire is bonded onto the polyamide nylon centre making the castor strong and durable. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

	Bearing Type	Roller
	Colour	No
	Hardness of Tread	D60
	Load Capacity (kg)	400
	Manufacturer Part No.	TSZ7 NPR 200/50 P3 BP
	Max Load Capacity of 4 Castors	1200
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	167
	Temperature Range	-40 min to +80 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	50
	Wheel Centre	White Polyamide
	Wheel Colour	Maroon
	Wheel Diameter(mm)	200
	Wheel Material	Polyurethane

Dimensions

