





















200mm Swivel Braked Castor Black Rubber Wheel

200-3360-PVR/SWB

This 200mm braked castor is made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The swiveling castor, with the black rubber wheel and a brake is suitable for trolleys, equipment machinery and general purposes. The black rubber wheel with roller bearings means the castor is quiet and easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

| | | |
|---|--------------------------------|--------------------|
|  | Bearing Type | Roller |
|  | Colour | No |
|  | Hardness of Tread | A85 |
|  | Load Capacity (kg) | 200 |
|  | Max Load Capacity of 4 Castors | 600 |
|  | Plate Dimension Length (mm) | 137 |
|  | Plate Dimension Width (mm) | 105 |
|  | Plate Hole Centres Length (mm) | 105 |
|  | Plate Hole Centres Width (mm) | 80/75 |
|  | Plate Hole Diameter | 10 |
|  | Product Type | Top Plate Castors |
|  | Swivel Radius | 167 |
|  | Temperature Range | -20 min to +80 max |
|  | Thread Material | No |
|  | Total Castor Height | 240 |
|  | Tread Width (mm) | 33 |
|  | Wheel Centre | Red Polypropylene |
|  | Wheel Colour | Black |
|  | Wheel Diameter(mm) | 200 |
|  | Wheel Material | Rubber |

Dimensions

