





















200mm Blue Elastic Rubber Castors with Brake 400kg

200-3360-RNB/SWB

These 200mm braked castors are made of a zinc plated housing which ensures the castors are robust enough and suitable for a variety of environments. The swiveling castor, with the non marking 8" blue rubber wheel and a brake is suitable for trolleys, equipment and general purposes. The non marking blue rubber caster wheel with roller bearings means these castors are quiet to move, will not mark the floor and will carry significant loads of up to 400kgs each. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	Blue
	Hardness of Tread	A70
	Load Capacity (kg)	400
	Manufacturer Part No.	TSZ7 NER 200/45 P3 BP 5017
	Max Load Capacity of 4 Castors	1200
	Plate Dimension Length (mm)	137
	Plate Dimension Width (mm)	105
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	167
	Temperature Range	-20 min to +80 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	40
	Wheel Centre	Black Polypropylene
	Wheel Colour	Blue
	Wheel Diameter(mm)	200
	Wheel Material	Rubber

Dimensions

