





















200mm Heavy Duty Castors Polyurethane Wheel 500kg

200-5000-HRT/SWB

This extra heavy duty castors are able to carry 500kgs each, overall height 240mm, 4 x M10 Bolt Fixing Plate, these lockable castors made of a heavy duty pressed steel zinc plated, housing a solid 200mm rubber wheel mounted on an aluminum centre. These industrial castor wheels runs on ball journal bearings, making the heavier loads easier to move. The foot operated wheel brake simultaneously brakes both the swivel castor head and the wheel. These heavy duty castors are suitable for a range of heavy industrial applications.



Technical Specifications

	Bearing Type	Ball Journal
	Colour	No
	Hardness of Tread	A67
	Load Capacity (kg)	500
	Max Load Capacity of 4 Castors	1500
	Plate Dimension Length (mm)	140
	Plate Dimension Width (mm)	110
	Plate Hole Centres Length (mm)	105
	Plate Hole Centres Width (mm)	80/75
	Plate Hole Diameter	10
	Product Type	Top Plate Castors
	Swivel Radius	160
	Temperature Range	-20 min to +85 max
	Thread Material	No
	Total Castor Height	240
	Tread Width (mm)	50
	Wheel Centre	Aluminum
	Wheel Colour	Black
	Wheel Diameter(mm)	200
	Wheel Material	Rubber

Dimensions

