




















80mm Fixed Castor Red Polyurethane Wheel 80-3368-PNB MAROON



This 80mm fixed polyurethane castors are made of a zinc plated housing which ensures the castor is robust enough and suitable for a variety of environments. The fixed castor, with the polyurethane wheel is strong and durable and suitable for moving machinery and equipment. The polyurethane tire is bonded onto the polyamide nylon centre making the castor strong and durable. Fixed castors can be teamed up with swiveling and braked castors for maximum control when moving.

Technical Specifications

| | | |
|---|--------------------------------|--------------------|
|  | Bearing Type | Roller |
|  | Colour | No |
|  | Hardness of Tread | D60 |
|  | Load Capacity (kg) | 100 |
|  | Max Load Capacity of 4 Castors | 300 |
|  | Plate Dimension Length (mm) | 99 |
|  | Plate Dimension Width (mm) | 85 |
|  | Plate Hole Centres Length (mm) | 80/77 |
|  | Plate Hole Centres Width (mm) | 60 |
|  | Plate Hole Diameter | 8 |
|  | Product Type | Top Plate Castors |
|  | Temperature Range | -40 min to +80 max |
|  | Thread Material | No |
|  | Total Castor Height | 108 |
|  | Tread Width (mm) | 38 |
|  | Wheel Centre | White Polyamide |
|  | Wheel Colour | Maroon |
|  | Wheel Diameter(mm) | 80 |
|  | Wheel Material | Polyurethane |

Dimensions

