




















JA 80mm Medium Duty Jacking Castor with Brake Rubber Wheel 70kg Load

JA4-080-GVR/SWB

This medium duty jacking castor with a brake and a 80mm rubber wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit. The foot operated brake will brake the castor swivel head and wheel.



Technical Specifications

	Bearing Type	Roller
	Bolt Hole Size (mm)	10
	Colour	No
	Jacking Unit Extension Height Max 76m	394
	Jacking Unit Height From Plate Lower Bolt Hole	187
	Load Capacity (kg)	70
	Max Load Capacity for 2 Jacking Castors	70
	Min Jacking Unit Extension Height	318
	Operating Method	24mm Spanner
	Plate Dimension Length (mm)	130
	Plate Dimension Width (mm)	75
	Plate Hole Centres Length (mm)	102
	Plate Hole Centres Width (mm)	51
	Plate Hole Diameter	11
	Product Type	Jacking Castors
	Swivel Radius	124
	Thread Material	No
	Total Castor Height	108 + 76
	Total Height to Plate Lower Bolt Hole	131
	Tread Width (mm)	27
	Wheel Centre	Black Polypropylene
	Wheel Colour	Grey
	Wheel Diameter(mm)	80
	Wheel Material	Rubber

Dimensions

