
























## JA6SUB

### Heavy Duty Jacking Castor Swivel Polyurethane Wheel 150mm 750kg |

This Extra Heavy Duty Jacking Castor with a 150mm heavy duty polyurethane wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit.

#### Technical Specifications

 Castor Type	Jacking Castors
 Bearing Type	Roller
 Load Capacity	1600
 Product Type	simple
 Technical PDF	JA6-150-SUB-compressed.pdf
 Tread Width (mm)	50
 Bolt Hole Size	12
 Max Load Capacity for 2 Jacking Castors	1500
 Total Height to Plate Lower Bolt Hole	225
 Jacking Unit Height From Plate Lower Bolt Hole	240
 Jacking Unit Height When Extended (76mm)	580
 Plate Length (mm)	152
 Plate Width (mm)	106
 Plate Hole Centres Length (mm)	114
 Plate Hole Centres Width (mm)	64
 Plate Hole Diameter	13
 Operating Method	Spanner
 Swivel Radius	135
 Total Castor Height	465
 Wheel Colour	Yellow
 Wheel Material	Polyurethane
 Wheel Centre	Cast Iron
 Wheel Diameter (mm)	150

