



















## 200mm Heavy Duty Jacking Castor with Polyurethane Wheel 1000kg Load

### JA8-200-SUB

This Extra Heavy Duty Jacking Castor with a 200mm heavy duty polyurethane wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit. JA8SUB



### Technical Specifications

	Bearing Type	Roller
	Bolt Hole Size (mm)	12
	Colour	No
	Jacking Unit Extension Height Max 76m	620
	Jacking Unit Height From Plate Lower Bolt Hole	240
	Load Capacity (kg)	1000
	Max Load Capacity for 2 Jacking Castors	1000
	Min Jacking Unit Extension Height	505
	Operating Method	Spanner
	Plate Dimension Length (mm)	152
	Plate Dimension Width (mm)	106
	Plate Hole Centres Length (mm)	114
	Plate Hole Centres Width (mm)	64
	Plate Hole Diameter	13
	Product Type	Jacking Castors
	Swivel Radius	165
	Thread Material	No
	Total Castor Height	226.5+ 76
	Total Height to Plate Lower Bolt Hole	265
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	200
	Wheel Material	Polyurethane

### Dimensions

